


# FontexX ES-series



## Electric scissor ES-series Due to Highly efficient design

- True Zero inside turning radius
- Extended duty cycle, more than 12 hours far more than the average 8 hours of similar products
- Zero-emission electric operation
- Great gradeability (more than 25%)



1. True Zero inside turning radius;
2. Hand rails are easy to fold down by 4 simple and solid lock-pins;
3. The machine is forkliftable in any directions and anywhere also fork pocket;
4. There are swing doors on both sides, so components are easy to repaired;
5. Good gradeability
6. There is good clearance between platform and extension platform for cleaning;
7. The console box with spiral wire so that it can be moved to any place even 2 meter away from machine;



# ES-series

Technical information

**FontexX**  
Cranes & Access

Model	ES1930	ES1932	ES2032	ES2632	ES3232	ES2646	ES3246	ES4046	ES4655
Platform Height	19ft	19ft	20ft	26ft	32ft	26ft	32ft	40ft	46ft
	6m	6m	6.1m	8m	10m	8m	10m	12m	14m
Platform Capacity	500lb	500lb	500lb	500lb	500lb	1000lb	700lb	700lb	500lb
	230kg	230kg	230kg	230kg	230kg	450kg	320kg	320kg	230kg
Platform Extension Capacity	250lb	250lb	250lb	250lb 2	50lb	250lb	250lb	250lb	250lb
	113kg	113kg	113kg	113kg	113kg	113kg	113kg	113kg	113kg
Overall Length	5ft 11in	5ft 11in	8ft	8ft	8ft	8ft	8ft	8ft	9ft4in
	1.80m	1.80m	2.44m	2.44m	2.44m	2.44m	2.44m	2.44m	2.84m
Overall Width	2ft 6in	2ft 8in	2ft 8in	2ft 8in	2ft 8in	3ft 10in	3ft 10in	3ft 10in	4ft 7in
	0.76m	0.81m	0.81m	0.81m	0.81m	1.17m	1.17m	1.17m	1.39m
Height -Stowed (Rails Folded)	5ft 11in	5ft 11in	5ft 11in	5ft 8in	6ft 1in	5ft 9in	5ft 9in	6ft 2in	6ft 2in
	1.8m	1.8m	1.8m	1.73m	1.86m	1.75m	1.75m	1.88m	1.87m
Height -Stowed (Rails Unfolded)	7ft 10in	7ft 10in	7ft 10in	7ft7in	8ft	8ft	8ft	8ft 6in	8ft 5in
	2.16m	2.16m	2.16m	2.31m	2.45m	2.45m	2.45m	2.58m	2.57m
Wheelbase	4ft 4in	4ft 4in	4ft 4in	6ft	6ft	6ft	6ft	6ft	7ft5in
	1.32m	1.32m	1.32m	1.85m	1.85m	1.85m	1.85m	1.85m	2.25m
Platform Length	5ft 5in	5ft 5in	5ft 5in	7ft 5in	7ft 5in	7ft 5in	7ft 5in	7ft 5in	8ft 8in
	1.65m	1.65m	1.65m	2.25m	2.25m	2.25m	2.25m	2.25m	2.65m
Platform Width	2ft 5in	2ft 5in	2ft 5in	2ft 8in	2ft 8in	3ft 8in	3ft 8in	3ft 8in	3ft 8in
	0.74m	0.74m	0.74m	0.81m	0.81m	1.12m	1.12m	1.12m	1.12m
Ground Clearance	2.36in	2.36in	2.36in	3.94in	3.94in	3.94in	3.94in	3.94in	3.94in
	0.06m	0.06m	0.06m	0.1m	0.1m	0.1m	0.1m	0.1m	0.1m
Drive Speed-Stowed	2.8mph	2.8mph	2.8mph	2.5mph	2.5mph	2.5mph	2.5mph	2.5mph	2.5mph
	4.5km/h	4.5km/h	4.5km/h	4km/h	4km/h	4km/h	4km/h	4km/h	4km/h
Drive Speed-Raised	0.5mph	0.5mph	0.5mph	0.5mph	0.5mph	0.5mph	0.5mph	0.5mph	0.5mph
	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h
Raise/Lower Speed	22s/24s	22s/24s	22s/24s	40s/35s	40s/35s 4	0s/35s	60s/40s	75s/50s	85s/60s
Batteries	4x6V/225Ah	4x6V/225Ah	4x6V/225Ah	4x6V/225Ah	4x6V/225Ah	4x6V/225Ah	4x6V/225Ah	4x12V/300Ah	4x12V/300Ah
Gradeability	25%	25%	25%	25%	25%	25%	25%	25%	25%
Weight (CE)	3130lb	3196lb	4012lb	4298lb	5180lb	4960lb	4849lb	6458lb	7054lb
	1420kg	1450kg	1820kg	1950kg	2350kg	2250kg	2200kg	2930kg	3200kg



**Fontexx Sales**  
Industrieweg 20  
5571 LJ Bergeijk  
The Netherlands

**T** +31 (0)497 726 926  
**F** +31 (0)497 726 927  
**E** info@fontexx.com  
**I** www.fontexx.com

**IBAN** NL82 INGB 0006 6833 96  
**BIC** INGBNL2A  
**Chamber of Commerce** 61774707  
**VAT** NL 854 482 623 B01